



Hitched to any mini-tractor, HS/R 14 will provide economical and excellent grass maintenance for sports fields, road-sides and parks.

Flexible, maneuverable, functional, with or without rollers.

Fast-rotating sharp swing-back blades. Stepless height adjustment.

Tractor PTO drive (540 rpm) protected by shear bolt torque limiter.

Model HS/R14	 L x W x H (cm)		 Hp		
HS14/90	133 x 113 x 88	90 (3ft)	25-35	2	110
HSR14/90	162 x 113 x 90	90 (3ft)	25-35	2	140
HS14/120	154 x 142 x 88	120 (4ft)	35-47	2	160
HSR14/120	183 x 142 x 90	120 (4ft)	35-47	2	190

**All measurement in cm*

ADDITIONAL INFO

3-Point Lingkage, CAT : I/II
 Universal Driveshaft : A4 c/w Shearbolts Torque Limiter
 Blade Speed at 540 rpm : 1042
 Cutting Heights, cm : 1-10
 Size of Blades, mm : 65 x 8
 With Front and Rear Roller : HS14/90 (NO), HSR14/90 (YES),
 HS14/120 (NO), HSR14/120 (YES)
 Type of Blade : Cranked and Swing



Swing-Back Blade



Changeable roller kit



Blade



The most versatile slasher for general grass and weed control, HS/R 24 is designed for the medium-duty tractor range. Suitable for grass cutting on a continuous basis, thus providing a very short pay-back time for professional contracting jobs.

Blades are designed to lift grass prior to cutting. A6 Universal Driveshaft with shear bolt protection. Easily can fix front and rear roller.

Speed and economic consideration prevail, rotaslashing is superior. Moreover, slashed clippings are thoroughly smashed: decompose faster-adding nutrients to soil, and should, as a general rule, therefore not be removed.

Model HS/R24	 L x W x H (cm)	 120 (4ft) 150 (5ft)	 Hp 35-45 45-60	 N. 2	 KG 190 220 250 280
HS24/120	156 x 143 x 89	120 (4ft)	35-45	2	190
HSR24/120	184 x 143 x 91	120 (4ft)	35-45	2	220
HS24/150	178 x 170 x 89	150 (5ft)	45-60	2	250
HSR24/150	207 x 170 x 91	150 (5ft)	45-60	2	280

*All measurement in cm

ADDITIONAL INFO

3-Point Linkage, CAT : I/II
 Universal Driveshaft : A6 c/w Shearbolts Torque Limiter
 Blade Speed at 540 rpm : 1042
 Cutting Heights, cm : 1-10
 Size of Blades, mm : 90 x 8
 With Front and Rear Roller : HS24/120 (NO), HSR24/120 (YES),
 HS24/150 (NO), HSR24/150 (YES)
 Type of Blade : Cranked and Swing



Swing-Back Blade



Changeable roller kit



Blade



A heavy-duty performer, HS/R34 is equally suitable for roadside and plantations maintenance as for undergrowth clearing.

Fitted with clutch protection, this machine is capable of slashing bushes and small trees. Heavy-duty blades, mounted in a hardened journal - swing back if hitting major objects. Universal PTO drive shaft with clutch.

Model HS/R34	 L x W x H (cm)		 Hp	 N.	 KG
HS34/150	171 x 171 x 101	150 (5ft)	60-90	2	300
HSR34/150	203 x 171 x 101	150 (5ft)	60-90	2	340
HS34/180	201 x 196 x 105	180 (6ft)	70-95	2	380
HSR34/180	232 x 196 x 105	180 (6ft)	70-95	2	440

**All measurement in cm*

ADDITIONAL INFO

3-Point Lintage, CAT : I/II
 Universal Driveshaft : A6 c/w FF2 Slip Clutch
 Blade Speed at 540 rpm : 778
 Cutting Heights, cm : 1-10
 Size of Blades, mm : 75 x 12
 With Front and Rear Roller : HS34/150 (NO), HSR34/150 (YES),
 HS34/180 (NO), HSR34/180 (YES)
 Type of Blade : Cranked and Swing



Beam



Changeable roller kit



Blade



As a general rule, this machine will deal effectively with any jungle undergrowth which a tractor can ride over. HS 44 is also widely used for stubble shaving, ratooning, and mulching of fibrous crops such as sugarcane and pineapple.

Chain slashing Heads and Disc Stubble Shaver available as optional.

Extra Heavy Duty Machine that will Continuously and uncompromisingly stand up to the most demanding land clearing tasks. Drive train protected by metal wearing disc and four bronze friction discs.

Model HS/R44	 L x W x H (cm)		 Hp	 N.	 KG
HS44/150	201 x 166 x 108	150 (5ft)	> 70	2	340
HSR44/150	225 x 166 x 108	150 (5ft)	> 70	2	370
HS44/180	211 x 197 x 108	180 (6ft)	> 70	2	490
HSR44/180	236 x 197 x 108	180 (6ft)	> 70	2	520

*All measurement in cm

ADDITIONAL INFO

3-Point Linkage, CAT : I/II

Universal Driveshaft : A7 PTO Drive Shaft Assembled with Sintered Metal Disc Slip Clutch Assy

Blade Speed at 540 rpm : 1026

Cutting Heights, cm : 1-10

Size of Blades, mm : 75 x 12

With Front and Rear Roller : HS44/150 (NO), HSR44/150 (YES),
HS44/180 (NO), HSR44/180 (YES)

Type of Blade : Cranked and Swing

