



B-16 is suitable on small farms, in paddy fields and in cash crops agriculture for primary and secondary tillage. With optional bed-former, it is equally useful for furrowing and preparing dry-land seedbeds for vegetable farming. Compact and lightweight—with low horsepower requirement. Bearings and other bought-in components are sourced from renowned international manufacturers.

Model B16	 L x W x H (cm)		 Hp	 N.	 KG
105	124 x 96 x 94	105 (40")	25	24	270
125	149 x 96 x 94	125 (50")	28-37	30	290
155	174 x 96 x 94	155 (60")	40-47	36	310
180	199 x 96 x 94	180 (70")	47-55	42	340

*All measurement in cm

ADDITIONAL INFO

3-Point Linkage, CAT : I/II
 Universal Driveshaft : A4 c/w Shearbolts Torque Limited
 Gearbox : Single Speed
 No. of Flanges : 105 (5), 125 (6), 155 (7), 180 (8)
 Size of Blades, mm : 75 x 6
 Rotor speed at 540 rpm : 210
 Side Transmission Drive : Rollerchain & Sprocket
 Max. Working Depth, cm : 16
 Type of Blade : L or C (Optional)



PTO Drive Shaft



L/C Blade



Face Seal



Model B-26 requires min. 45 hp and is designed for general soil preparation in wet or dry-land conditions. With multispeed gear-setting, B-26 provides a wide choice of tillage suit crop, soil and climate.

Powerful transmission with inbuilt safety features - to protect machine and tractor against shock-loads.

A popular workhorse for contractors, its many features are neatly incorporated in a simple design user-friendly and easy to maintain.

All models come with metal to metal face seals to prevent water from contaminating transmission oil when working in wet conditions.

Selectatilt pick-off gears allow four alternative rotor speeds (540 PTO)

Model B26	 L x W x H (cm)	 155 (60")	 Hp	 N.	 KG
155	174 x 100 x 100	155 (60")	45-60	36	370
180	199 x 100 x 100	180 (70")	55-75	42	410
205	230 x 100 x 100	205 (80")	70-80	48	450
230	250 x 100 x 100	230 (90")	75-90	54	490

**All measurement in cm*

ADDITIONAL INFO

- 3-Point Lingkage, CAT : I/II
- Universal Driveshaft : A6 c/w FF2 Slip Clutch
- Gearbox : Multi Speed
- No.of Flanges : 155 (7), 180 (8), 205 (9), 230 (10)
- Size of Blades, mm : 90 x 6
- Rotor speed at 540 rpm : 158/176/221/247 Multispeed (16T, 17T, 19T, & 20T)
- Side Transmission Drive : Rollerchain & Sprocket
- Max. Working Depth, cm : 18
- Type of Blade : L or C (Optional)





This extra-heavy-duty rotavator performs excellently in demanding conditions and is ideal for "built-on" combinations such as Bedformer, Furrower or Crumble Roller.

Side drive through heavy-duty Roller Chain - 17 ton breaking load - with externally adjustable tensioning skid. Rotor drive is supported by large ball bearings and face seals.

Protection of tractor and transmission against shock-loads ensured by heavy-duty safety clutch. Cultivating depth is adjustable by raising or lowering the side skids.

Selectatilt pick-off gears allow four alternative rotor speeds (540 PTO)

Model B36	 L x W x H (cm)		 Hp	 N.	 KG
155	180 x 103 x 110	155 (60")	50-60	36	470
180	206 x 103 x 110	180 (70")	60-75	42	510
205	232 x 103 x 110	205 (80")	70-90	48	550
230	258 x 103 x 110	230 (90")	85-110	54	590
255	283 x 103 x 110	255 (100")	90-110	60	360

**All measurement in cm*

ADDITIONAL INFO

3-Point Linkage, CAT : I/II
 Universal Driveshaft : A8c/w FF4 Slip Clutch
 Gearbox : Multi Speed
 No. of Flanges : 155 (7), 180 (8), 205 (9), 230 (10), 255 (11)
 Size of Blades, mm : 90 x 6
 Rotor speed at 540 rpm : 133/165/204/252 Multispeed (16T, 18T, 20T, & 22T)
 Side Transmission Drive : Rollerchain & Sprocket
 Max. Working Depth, cm : 18
 Type of Blade : L or C (Optional)



PTO Drive Shaft



L/C Blade



Face Seal