

 **KUBOTA**

EK

EK5 PRO SERIES TRACTOR

EK5-901 PRO 4WD

BASIC · RELIABLE · POWERFUL



BASIC • RELIABLE • POWERFUL

EK5-901 PRO 4WD

ENGINE

4 Cylinder, turbo charged, intercooler, direct injection engine

- Ease of all applications without engine RPM drop.
- More output & more saving with better fuel economy.



COMFORT

Power steering

The power steering reduces operator fatigue even during long working hours.

Side shift gear levers

Ergonomically placed gear levers for better comfort and easy operation.

Full flat platform

The wider leg room offers an operator greater comfortability.

FUNCTIONALITY

Transmission

Synchro Mesh Transmission with 12 Forward + 12 Reverse with Synchro Shuttle.

Hydraulic System

2 single & double acting convertible auxiliary valve.

Multi disc oil immersed brakes (OIB)

Efficient brakes on roads with heavy loads. Enhanced life with low maintenance cost.

Front & rear work lights

Bright Front & rear work lights provide plenty of illumination for night-time tasks.

Double clutch for independent PTO

Easy cut-off PTO power while on turns during PTO operation. Gives comfort to operator and enhances clutch life.



3-point hitch

The category II 3-point hitch provides fast and simple attachment of rear-mounted implements.

Lift capacity

2500 kg Lifting capacity at lower link end.

Specifications

Model	EK5-901 PRO 4WD	
Engine		
Model	E4.368TCI	
Make	Escorts Kubota	
Number of cylinders	4	
Engine Gross Power	HP	90
Displacement	cc	3680
Rated RPM	rpm	2200
Fuel tank capacity	ℓ	75
Air cleaner	Dry, dual	
Transmission		
Gear	F12 / R12	
Type	Synchro Mesh	
Clutch type	Double	
Brake type	Wet disc (OIB)	
Max. traveling speed		
Forward	km/h	37.8
Reverse	km/h	28.3
PTO		
Speed	rpm	540 / 540E
Output	HP	73.5
Type	Independent & Ground PTO	

3-point hitch	Cat. II	
Hydraulics		
Control system	Draft & position	
Lift capacity (at lower link end)	kg	2500
Lift capacity (at 610mm behind lifting pt.)	kg	1219
Auxiliary valve	2 single & double acting (convertible)	
Steering	Power steering	
Tyre		
Front standard tyre	12.4-24, R1	
Rear standard tyre	18.4-30, R1	
Dimensions		
Overall length	mm	4220
Overall width	mm	2425
Overall height	mm	2580 (upto ROPS)
Wheel base	mm	2300
Ground clearance	mm	428 (below rear axle housing)
Front tread width	mm	1540 - 1900
Rear tread width	mm	1508 - 1908
Turning radius w/o brake	m	4.6
Tractor weight (Unballasted)	kg	3265
(Fully ballasted)	kg	3673

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. For complete operational information, the operator's manual should be consulted.

Manufactured by:

ESCORTS KUBOTA LIMITED

Marketed by:

KUBOTA Corporation

Distributed by:

KUBOTA Malaysia Sdn Bhd

Lot 766, Jalan Subang 4, Subang Penaga Industrial Park, 47500 Subang Jaya, Selangor Darul Ehsan, Malaysia

Tel: 03 7890 3533 Email: kmsb_g.sales@kubota.com

Website: www.kubotamalaysia.com