



For Earth, For Life  
Kubota

**EK**

**EK5 PRO SERIES TRACTOR**  
**EK5-901 PRO 4WD**  
**BASIC . RELIABLE . POWERFUL**





# BASIC • RELIABLE • POWERFUL

## EK5-901 PRO 4WD

### ENGINE

#### 4 Cylinder, turbo charged, intercooler, direct injection engine

- Ease of all applications without engine RPM drop.
- More output & more saving with better fuel economy.



### COMFORT

#### Power steering

The power steering reduces operator fatigue even during long working hours.

#### Side shift gear levers

Ergonomically placed gear levers for better comfort and easy operation.

#### Full flat platform

The wider leg room offers an operator greater comfortability.

### FUNCTIONALITY

#### Transmission

Synchro Mesh Transmission with 12 Forward + 12 Reverse with Synchro Shuttle.

#### Hydraulic System

2 single & double acting convertible auxiliary valve.

#### Multi disc oil immersed brakes (OIB)

Efficient brakes on roads with heavy loads. Enhanced life with low maintenance cost.

#### Front & rear work lights

Bright Front & rear work lights provide plenty of illumination for night-time tasks.

#### Double clutch for independent PTO

Easy cut-off PTO power while on turns during PTO operation. Gives comfort to operator and enhances clutch life.



EK5-901 PRO model shown

		EK5-901 PRO	
		4WD	
Engine power @ rated rpm	HP	88	
PTO speed	rpm	540/540E	
Max. traveling speed	km/h	37.8	
Tilt steering		-	
3-point hitch external adjustment lever		-	
Smart lift		-	
Front fenders		-	
Fuel tank capacity	ℓ	75	
Tractor weight (Unballasted)	kg	3265	

#### 3-point hitch

The category II 3-point hitch provides fast and simple attachment of rear-mounted implements.

#### Lift capacity

2500 kg Lifting capacity at lower link end.



### Specifications

Model	EK5-901 PRO 4WD	
<b>Engine</b>		
Model	E4.368TCI	
Make	Escorts Ltd.	
Number of cylinders	4	
Engine power @ rated rpm	HP	88
Displacement	cc	3680
Rated RPM	rpm	2200
Fuel tank capacity	ℓ	75
Air cleaner	Dry, dual	
<b>Transmission</b>		
Gear	F12 / R12	
Type	Synchro Mesh	
<b>Clutch type</b>	Double	
<b>Brake type</b>	Wet disc (OIB)	
<b>Max. traveling speed</b>		
Forward	km/h	37.8
Reverse	km/h	28.3
<b>PTO</b>		
Speed	rpm	540 / 540E
Output	HP	73.5
Type	Independent & Ground PTO	

<b>3-point hitch</b>	Cat. II	
<b>Hydraulics</b>		
Control system	Draft & position	
Lift capacity (at lower link end)	kg	2500
Lift capacity (at 610mm behind lifting pt.)	kg	1219
Auxiliary valve	2 single & double acting (convertible)	
Steering	Power steering	
<b>Tyre</b>		
Front standard tyre	12.4-2.4, R1	
Rear standard tyre	18.4-30, R1	
<b>Dimensions</b>		
Overall length	mm	4220
Overall width	mm	2425
Overall height	mm	2700
Wheel base	mm	2300
Ground clearance	mm	405
Front tread width	mm	1540 - 1900
Rear tread width	mm	1508 - 1908
Turning radius w/o brake	m	4.6
Tractor weight (Unballasted)	kg	3265
(Fully ballasted)	kg	3533

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. For complete operational information, the operator's manual should be consulted.



#### KUBOTA Malaysia Sdn Bhd

Lot 766, Jalan Subang 4,  
Sungai Penaga Industrial Park, 47500 Subang Jaya,  
Selangor Darul Ehsan, Malaysia  
Tel: 03 7890 3533 Email: kmsb\_g.sales@kubota.com

Website: [www.kubotamalaysia.com.my](http://www.kubotamalaysia.com.my)

