



For Earth, For Life
Kubota

SK

KUBOTA IMPLEMENT FRONT END LOADER & BACKHOE LOADER

Designed especially for Kubota Tractors to deliver superior performance and versatility, perfect for landscaping, construction and general farm usage.



FRONT END LOADER

TRACTOR MODEL	B2320	L3200, L3540	L3800, L4400	L4740	M6040	M8540, M9540	M108S
MODEL	HL1564	HL1700	HL1800	HL1900	HL2100	HL2400	HL2600
Max. Lift Height, mm	1995	2139	2269	2390	2704	2966	3417
Max. Dump Angle, °	50	50	47	52.7	55	55	48.4
Bucket Depth L x W x H, mm	598 x 453 x 487	578 x 453 x 421	717 x 512 x 496	717 x 512 x 496	850 x 640 x 561	850 x 640 x 561	844 x 595 x 547
Lift Capacity, kg w/o bucket	547	560	1251	1198	1564	1897	1865
Bucket Capacity, m ³	0.14	0.17	0.32	0.35	0.49	0.65	0.56
Bucket Cylinder, mm	30 x 45 x 550 x 311ST	30 x 45 x 589 x 311ST	35 x 60 x 674 x 363ST	35 x 60 x 729 x 363ST	35 x 65 x 1110 x 340ST	40 x 80 x 1258 x 414ST	40 x 80 x 1372 x 419ST
Loader Weight, kg	236	337	426	401	728	980	980

BACKHOE LOADER




TRACTOR MODEL	B2320/ L3200/ 3800/ 3540
MODEL	STB30
Digging Depth	1768 mm
Backhoe Reach	2507 mm
Loading Height	2202 mm
Swing Arc	1909 mm
Bucket Rotation	1919 mm
Bucket Cylinder Digging Force	978 kgf

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact us for warranty information.

For complete operational information, the operators manual should be consulted.

KUBOTA MALAYSIA SDN BHD

Lot 766, Jalan Subang 4, Off Persiaran Subang
Sungai Penaga Industrial Park, 47500 Subang Jaya
Selangor Darul Ehsan, Malaysia
Tel: 603-78903533
E-mail: kmsb_g.sales@kubota.com

 www.kubotamalaysia.com.my
 KubotaMalaysiaSB
 Kubota Malaysia

